

## Research on NTN Technology for 5G evolution & 6G

*Yuki Hokazono, Yoshihisa Kishiyama, and Takahiro Asai*

### Abstract

In the 5th-generation mobile communication system (5G) evolution & 6G, extreme coverage extension is being studied for use cases in all places including air, sea, and space. Non-terrestrial networks using geostationary satellites, low earth orbit satellites, and high-altitude platform stations are promising tools for providing high-quality communication services in areas that cannot be covered by the conventional mobile communication network. In this article, we describe these technologies and the details of a 39-GHz band airborne propagation measurement experiment performed using a small airplane at an altitude of about 3 km.

*Keywords: NTN, HAPS, extreme coverage extension*

### 1. Introduction

While the 5th-generation mobile communication system (5G) is expected to be an important technology for regional development and solving regional issues, a key issue for the 5G evolution and 6G era is

expected to be expanding the communication area to any place where its benefits can be enjoyed [1]. As shown in **Fig. 1**, NTT DOCOMO is conducting research and development aimed at achieving extreme coverage extension whereby mobile communication can be made available in all locations,



Fig. 1. Extreme coverage extension.




Fig. 2. Illustration of how satellites and HAPS can be used to extend coverage to the sky, sea, and space.

including the air, sea, and space, that are not adequately covered by conventional mobile communications networks, thereby extending coverage to drones, flying cars, ships, and even space stations.

To achieve this extreme coverage extension, we are focusing on non-terrestrial network (NTN)<sup>\*1</sup> technology using satellites and high-altitude platform stations (HAPS)<sup>\*2</sup>. This technology is able to provide communication coverage in mountainous and remote areas, at sea, and even in outer space by employing satellites and HAPS systems that are free of geographical restrictions.

This article describes extreme coverage extension, which is one of the key issues for the realization of 5G evolution & 6G. Specifically, we describe the concept of NTN technology, which has been attracting attention as a promising approach, the use cases and technical issues of wireless system technology using HAPS, and our work on measuring the propagation of radio waves using a small aircraft.

## 2. Extreme coverage extension and NTN technology for 5G evolution & 6G

Extreme coverage extension supports use cases in any location, including air, sea, and space. This will extend coverage to users that cannot be covered by

conventional mobile communication networks, including drones, flying cars, ships, and space stations. To achieve extreme coverage extension, it will be necessary to develop technologies that facilitate highly efficient long-range wireless transmission over at least several tens of kilometers.

As shown in **Fig. 2**, by considering the use of (1) geostationary (GEO) satellites, (2) low earth orbit (LEO) satellites, and (3) HAPS, we will be able to cover mountainous and remote areas, the sea, the sky, and even outer space, and to provide communication services to these areas [2].

### (1) GEO satellite

A GEO satellite orbits the Earth at an altitude of about 36,000 km. Although the one-way radio wave propagation time between a GEO satellite and a ground station antenna is relatively long (about 120 ms), just three or four GEO satellites can provide the entire planet with constant coverage. Even today, GEO satellites are used to complement terrestrial

\*1 NTN: Any network in which the communication area is not limited to the ground but extended to other places such as the air, sea, and space through the use of non-terrestrial equipment such as satellites and HAPS.

\*2 HAPS: An airborne platform that is designed to operate in the stratosphere on board a vehicle such as a solar-powered aircraft or airship.

networks by providing a mobile backhaul<sup>\*3</sup>. Since additional network capacity will be required in the 6G era, very high throughput satellites are being studied with the aim of improving system capacity by optimizing the allocation of power and frequency across multiple beams [3].

## (2) LEO satellite

An LEO satellite orbits the Earth at an altitude ranging from a few hundred km to about 2000 km. Unlike a GEO satellite, it has a much lower orbit and a much smaller propagation delay (just a few ms for a one-way trip). LEO satellites are currently used for satellite mobile phone systems and satellite sensing<sup>\*4</sup>. They are also expected to be used for the expansion of communication capacity through the reduction of satellite fabrication costs and the use of multiple input, multiple output (MIMO)<sup>\*5</sup> technology, and for high-capacity, low-latency backhauls in satellite constellations that form networks through cooperation between multiple satellites [4].

## (3) HAPS

HAPS have recently attracted renewed attention due to their ability to be parked at an altitude of about 20 km in fixed locations, allowing them to provide services across terrestrial cells<sup>\*6</sup> with a radius of approximately 50 km or more [5]. Since their altitude is lower than that of LEO satellites, it is possible to achieve a one-way radio wave propagation time of about 0.1 ms, depending on the cell radius. As a result, they are considered to be an effective way of deploying services not only in regions that have been hit by natural disasters but also in many of the industrial use cases envisioned for 5G evolution & 6G.

The 3rd Generation Partnership Project (3GPP) has begun studying how satellites and HAPS can be used to extend New Radio (NR)<sup>\*7</sup> to NTN [6].

### 3. HAPS use cases and network configuration/control techniques

NTT DOCOMO is working on the research and development of communication methods and network architectures that can flexibly link 5G networks and other terrestrial networks with stratospheric HAPS networks [7, 8]. In addition to providing flexible support for a wide range of future use cases as envisioned in 5G evolution & 6G, this project is conducting studies aimed at the implementation of communication systems that use realistic HAPS in terms of development and operation costs.

### 3.1 HAPS use cases

As shown in **Fig. 3**, for the 5G evolution & 6G era, it is expected that various use cases will involve using HAPS to relay radio waves or emit radio waves as a base station. These use cases include fixed systems that provide services for backhaul applications, and mobile systems that provide services to terminals either directly or by via repeaters and relays. In particular, the use of broadband millimeter wave<sup>\*8</sup> radio signals is expected to enable the timely provision of high-speed, large-capacity, low-latency lines required for various applications including industry and public events, regardless of whether or not optical fibers or other wired networks are available, and in any location, including at sea, in the air, or in remote areas.

The requirements of HAPS systems can vary widely from one use case to the next. As shown in **Fig. 4**, different use cases require different communication speeds and different bandwidths. There is a need for flexible communication methods and systems that can support all use cases of fixed and mobile systems. For example, it is considered that the communication speed for backhaul applications to 5G base stations will have to be at least 1 Gbit/s per service link<sup>\*9</sup>. Furthermore, to provide multiple simultaneous service links, the feeder link<sup>\*10</sup> will have to be capable of even faster communication speeds (several Gbit/s to several tens of Gbit/s) and must operate as stably as possible regardless of weather-related effects.

It is also necessary to flexibly control lines so that

\*3 Backhaul: In a mobile communication network, a backhaul is a fixed line that supports high-speed, high-capacity transmission of information between a large number of wireless base stations and the core network.

\*4 Satellite sensing: Observing the state of the atmosphere and the Earth's surface from space by means of instruments carried on board satellites.

\*5 MIMO: A signaling technique whereby multiple transmit and receive antennas are used to transmit signals simultaneously and at the same frequency to improve communication quality and the efficiency of frequency utilization.

\*6 Cell: The unit of area division that makes up the service area of a mobile communications network.

\*7 NR: A radio system standard formulated for 5G. Compared with 4G, it enables faster communication by utilizing high frequency bands (e.g., 3.7 GHz and 28 GHz bands), and low latency and highly reliable communication for achieving advanced Internet of Things (IoT).

\*8 Millimeter waves: Radio signals in the frequency band from 30 GHz to 300 GHz as well as the 28 GHz band targeted by 5G all of which are customarily called "millimeter waves."

\*9 Service link: A communication path between a satellite or HAPS and a terminal in an NTN communication system.

\*10 Feeder link: A communication path between a satellite or HAPS and a terrestrial base station (gateway) in an NTN communication system.




Fig. 3. Various use cases expected for HAPS.




Fig. 4. Requirements for each HAPS use case.

they can be adapted from normal business applications to public safety<sup>\*11</sup> applications in the event of a disaster. Current disaster countermeasures are geared towards providing basic communication services

\*11 Public safety: A generic term for services that ensure the safety of the public, including disaster prevention, police, fire, and first-aid services.

such as voice calls and short message services, but in the future, it may also be necessary to consider use cases that require faster communication speeds, such as remote control of equipment at disaster sites, video transmission, and communication via drones. For disaster countermeasures, it will also be necessary to study network configurations and control techniques that assume the ability of a system to operate even if some devices become unavailable.

## 3.2 Technology for network configuration and control in conjunction with 5G networks

### 3.2.1 Classification of HAPS-mounted stations

In the network configuration and control technology used when implementing backhauled 5G base stations via HAPS, we are focusing on the categorization of HAPS-mounted stations. They can be roughly divided into two types: (1) relay stations, which receive signals from ground stations and relay them back to other ground stations after performing necessary processes such as frequency conversion, and (2) base stations, which are made by installing 5G network base station equipment (or at least part of it) in a HAPS.

#### (1) Relay station type

The relay type is effective when the number of on-board devices is relatively small and the size, weight, and power consumption of the HAPS-mounted station are strictly limited.

#### (2) Base station type

The base station type is formed by equipping a HAPS with an antenna device, together with many base station functions. The more of these functions it includes, the greater the amount of control that can be performed within the HAPS, making it possible to reduce the amount of feeder link information. On the other hand, installing more functions results in a station that is larger, heavier, and consumes more power.

In general, implementing more of the base station functions on the ground network side has the advantages of lower development costs and ease of operation, but implementing these functions on the HAPS results in greater resilience to natural disasters. In terms of performance, a HAPS-mounted station should at least implement some functions, such as beam control when using millimeter waves. It is also necessary to comprehensively study a wide range of requirements to be considered when incorporating HAPS systems into a 5G network. These include the size, weight, and power consumption of HAPS-equipped stations, their development and operation costs, the ability of these HAPS platforms can be

shared by fixed-line and mobile communication systems, and their ability to cooperate with GEO/LEO satellites.

### 3.2.2 Examples of network configuration in conjunction with the 5G network

An example of a HAPS base station in a network configuration linked to the 5G network is shown in **Fig. 5**. Here, the distributed unit (DU)<sup>\*12</sup> and radio unit (RU)<sup>\*13</sup> of the 5G base station are mounted on the HAPS in accordance with Open RAN (O-RAN)<sup>\*14</sup> Alliance specifications [9]. In this configuration, availability is ensured by installing a centralized unit (CU)<sup>\*15</sup> at a disaster-resistant point on the ground. Information received by the HAPS from the CU in the feeder link is transmitted via 5G radio to a small terrestrial base station device (relay station) in the service link, thereby enabling the use of portable 5G base stations without having to use a wired backhaul. In this configuration, it is also possible to provide direct communication from the HAPS to 5G terminals without the need for intervening relay stations. As a further extension, site diversity<sup>\*16</sup> can be implemented by using multiple CUs on the ground side to reduce the impact of bad weather and natural disasters, and mobility support<sup>\*17</sup> can be implemented by switching the communication target to a different HAPS when the terminal moves from one communication area to another.

In addition to the configuration shown in Fig. 5, we are also considering other promising configurations: one in which a HAPS is used to carry a standalone<sup>\*18</sup> 5G base station, and another with a relay-type configuration where a 5G radio repeater is installed in a HAPS. For each configuration, it is necessary to conduct a comprehensive study that takes account of

\*12 DU: A functional unit of a wireless base station that performs real-time data link layer control and other functions.

\*13 RU: The radio unit of a wireless base station.

\*14 O-RAN: An open, intelligent radio access network aimed at efficiently providing a variety of services in the 5G era.

\*15 CU: An aggregating node that implements functions such as non-real-time Layer 2 functions and RRC (radio resource control) functions in a radio base station.

\*16 Site diversity: A technique for improving communication quality by switching between multiple ground stations when radio waves are highly attenuated due to rain or obstacles.

\*17 Mobility support: Technology that allows communication to continue when a terminal moves across a communication area by switching it to a different base station before communication is interrupted.

\*18 Standalone: A deployment scenario using only NR, in contrast with non-standalone operation which uses Long Term Evolution (LTE)-NR Dual Connectivity to coordinate existing LTE/LTE-Advanced and NR.




Fig. 5. Example of cooperative configuration when HAPS is used for backhaul.

various attributes such as mobility support, site diversity technology and frequency sharing technology<sup>\*19</sup>, as well as HAPS installation requirements such as links with GEO/LEO satellites, the equipment weight and power consumption.

#### 4. Experimental 39 GHz band propagation measurements using a small aircraft

To implement a communication area from an airborne station in 5G evolution & 6G, we conducted an experimental demonstration of radio wave propagation measurements in an urban area (Odawara City, Kanagawa Prefecture), a mountain forest (Tanzawa), and a remote island (Izu Oshima) using a small aircraft (February 15–26, 2021) [10]. Before using the actual HAPS system, we performed an initial experiment to compare the propagation of millimeter wave (39 GHz band) radio signals, which are suitable for 5G high-speed communication, and signals at a lower frequency (2 GHz band), which propagate more easily than millimeter wave signals. These signals were sent from the ground to a receiver mounted on a small aircraft about 3 km above ground level. In the urban environment, we measured the effects of obstacles such as buildings and reflected waves. In the forest, we measured the effects of terrain and trees. And in the remote island, we measured the effects of clouds and low elevation angles above the sea. Our results

show that radio wave propagation in the 39 GHz and 2 GHz bands depends on various environmental factors, and changes when the airplane turns.

#### 4.1 Measurement environment and measured items

Figure 6 shows an illustration of the airborne propagation measurement test. The radio wave transmission points were located in an urban area (Odawara City in Kanagawa Prefecture), a forest (Tanzawa), and a remote island (Izu Oshima), and the reception point was a small aircraft circling with a radius of 1 to 2 km. The elevation angle of the small aircraft (receiving point) from the transmitting point was determined to be equivalent to the use case of a HAPS circling at an altitude of 20 km. Specifically, we assumed a coverage radius of 50 km for an altitude of 20 km in the urban and forest use cases (elevation angle: 21.8°), and a coverage radius of 200 km for an altitude of 20 km in the remote island use case (elevation angle: 5.7–11.5°). In addition to the line-of-sight environment, we also measured the received power with intervening obstacles such as buildings

\*19 Frequency sharing technology: Technology that makes it possible to share frequencies by suppressing the interference effects that occur when two systems use the same frequency at the same location. In this article, we are mostly concerned with frequency sharing between HAPS systems and terrestrial mobile communication systems.




Fig. 6. Illustration of the airborne propagation measurement test.



(a) Buildings in the urban test area



(b) Trees in the forest test area



(c) Mountains in the forest test area



(d) Clouds in the remote island test area

Fig. 7. Test environments with various obstacles.

and trees in each use case, as shown in **Fig. 7**.

For the transmitting antenna, we selected a product that was able to cover the turning range of the aircraft within the beam width<sup>\*20</sup>, and we fixed the direction of this antenna toward the aircraft's turning center. The receiving antenna was housed in a mounting frame, and a 3-mm-thick polycarbonate radome<sup>\*21</sup> designed to cause almost no propagation loss<sup>\*22</sup> was secured to its base. We also performed an initial

experiment in which neither of the transmitting or

\*20 Beam width: The antenna radiation angle at which the beam is radiated with gain of  $-3\text{dB}$  or less from the maximum antenna gain.

\*21 Radome: An enclosure to protect an antenna. These are made of materials that are transparent to radio waves.

\*22 Propagation loss: The amount of attenuation in the power of a signal emitted from a transmitting station until it arrives at a reception point.




Fig. 8. Propagation loss time series data in the 39 GHz band at Odawara City (line of sight)/2 km turning diameter.

receiving antennas were provided with tracking functions, and the receiving antenna was fixed directly to the underside of the aircraft.

## 4.2 Evaluation

### 4.2.1 Overview

From this experiment, we found that the maximum reception sensitivity in the unobstructed line-of-sight environments was almost identical to the value obtained by desktop calculations, while the loss of received power in the 39 GHz band was relatively large when there were intervening buildings and trees. To reduce the influence of obstacles of this sort, it will be necessary to consider adopting measures such as site diversity. We also confirmed that the influence of clouds was relatively small in the absence of rainfall.

Furthermore, since signals were transmitted and received in this experiment by means of antennas with the same directivity pattern regardless of the aircraft's position and flight attitude, it also became clear that the received power varies greatly with changes in the angle of the antenna caused by turning of the aircraft. For the practical use of HAPS in the future, these results confirm the importance of using control technology to suppress the effects of turning the aircraft and maintain a constant received power.

### 4.2.2 Experimental results in Odawara

As a concrete example of the measurement results, this section describes an experiment that models an urban use case. For the line-of-sight environment in Odawara City, Kanagawa Prefecture with the aircraft circling with a turning diameter of 2 km, **Figure 8**

shows the time series data of losses in the 39 GHz band. When the maximum receiver sensitivity in the 39 GHz band is calculated from the free space loss shown in Fig. 8, the results generally match the figures obtained in desktop calculations with an error of only about 1.2 dB. On the other hand, the time-series data fluctuated greatly when the aircraft turned, with the average received power decreasing by about 17 dB from the maximum value and the median decreasing by about 14 dB. It is thought that these reductions were mainly caused by fluctuations in the directive gain of the transmitting and receiving antennas, polarization losses<sup>\*23</sup>, and the obstruction of radio waves by the aircraft itself when the underside of the aircraft was facing away from the transmission point.

In the building-occluded environment, the 39 GHz propagation loss has a mean value about 17 dB larger and a median value about 19 dB larger compared with the line-of-sight environment. Although obstruction by buildings also affects the 2 GHz band, the losses are relatively small—about 8 dB in the average value and about 9 dB in the median value—compared with the line-of-sight environment. Furthermore, when the underside of the aircraft is tilted towards the transmitting point, the received power is at least 40 dB greater than when the aircraft is tilted in the other direction.

## 5. Conclusion

In this article, as part of our efforts toward implementing extreme coverage extension, which is one of

\*23 Polarization loss: A loss of power received by a receiving antenna that occurs due to the vibration direction (polarization) of the electric field when radio waves propagate in space.



the important issues for 5G evolution & 6G, we have described NTN technology, especially HAPS use cases and network configuration/control technology, and we have shown the results of airborne radio propagation tests performed using a small aircraft assuming HAPS use cases. NTT DOCOMO will continue developing NTN technology aimed at achieving extreme coverage extension and technology for realizing HAPS networks, and promoting demonstration experiments and standardization activities.

Finally, part of this research and development is carried out by the Ministry of Internal Affairs and Communications (Research and Development for Expansion of Radio Resources; JPJ000254).

This article is the reproduction of the special article published in NTT DOCOMO Technical Journal (Vol. 23, No. 2, Oct. 2021).

## References

- [1] NTT DOCOMO, “White Paper: 5G evolution and 6G,” Version 3.0, Feb. 2021.  
[https://www.nttdocomo.co.jp/english/binary/pdf/corporate/technology/whitepaper\\_6g/DOCOMO\\_6G\\_White\\_PaperEN\\_v3.0.pdf](https://www.nttdocomo.co.jp/english/binary/pdf/corporate/technology/whitepaper_6g/DOCOMO_6G_White_PaperEN_v3.0.pdf)
- [2] T. Onizawa, T. Tatsuta, N. Kita, and F. Yamashita, “Recent Research and Development in Fixed Wireless and Satellite Communication Systems,” IEICE Technical Report, Vol. 119, No. 31, RCS2019-32, pp. 53–58, May 2019.
- [3] J. Bejarano, C. Nieto, and F. Piñar, “MF-TDMA Scheduling Algorithm for Multi-Spot Beam Satellite Systems Based on Co-channel Interference Evaluation,” IEEE Access, Vol. 7, pp. 4391–4399, Dec. 2018.
- [4] B. Di, H. Zhang, L. Song, Y. Li, and G.Y. Li, “Ultra-dense LEO: Integrating Terrestrial-satellite networks into 5G and Beyond for Data Offloading,” IEEE Trans. Wireless Commun., Vol. 18, No. 1, pp. 47–62, Dec. 2018.
- [5] HAPS Alliance, “Introducing the HAPS Alliance.”  
<https://hapsalliance.org/>
- [6] 3GPP, RP-193234: “Solutions for NR to Support Non-terrestrial Networks (NTN),” Dec. 2019.
- [7] J. Suzuki, H. Kitanozono, T. Takamori, Y. Morita, Y. Kishiyama, T. Sotoyama, and R. Miura, “Development of a 38-GHz Band Wireless Communication System with High-altitude Platform Stations (HAPS) in Cooperation with 5G Networks: A Study of High-speed High-capacity Backhaul Lines for 5G Networks,” Proc. of 2021 IEICE General Conference, B-3-1, Mar. 2021.
- [8] Y. Hokazono, Y. Kishiyama, T. Asai, J. Suzuki, and H. Kitanozono, “Development of a 38-GHz Band Wireless Communication System with high-altitude Platform Stations (HAPS) in Cooperation with 5G Networks: A Study of HAPS Network Configuration and Control Technology,” Proc. of 2021 IEICE General Conference, B-3-2, Mar. 2021.
- [9] A. Umesh, T. Yajima, T. Uchino, and S. Okuyama, “Overview of O-RAN Fronthaul Specifications,” NTT DOCOMO Technical Journal, Vol. 21, No. 1, pp. 46–59, July 2019.
- [10] NTT DOCOMO Press Release, “Trial Measurements of 39 GHz Band Radio Propagation with a View to Serving Communication Areas with Airborne Systems,” Mar. 2021.

## Trademark notes

All company names or names of products, software, and services appearing in this article are trademarks or registered trademarks of their respective owners.



### Yuki Hokazono

Research Engineer, 6G-IOWN Promotion Department, NTT DOCOMO, INC.

He received a B.E. and M.E. from Graduate School of Engineering, the University of Tokyo, in 2017 and 2019. Since joining NTT DOCOMO in 2019, he has been involved in research and development activities related to radio frequency wireless technologies for 5G evolution & 6G, especially non-terrestrial networks. He also contributed to the 3GPP TSG-RAN WG1 as a delegate from NTT DOCOMO.



### Yoshihisa Kishiyama

Manager, 6G-IOWN Promotion Department, NTT DOCOMO, INC.

He received a B.E., M.E., and Ph.D. from Hokkaido University in 1998, 2000, and 2010. Since joining NTT DOCOMO in 2000, he has been involved in the research and development of 4G and 5G radio access technologies, including concept development, standardization, and trials. He is currently working on “5G evolution & 6G” and is the main author of “DOCOMO 6G White Paper.” He has more than 400 granted patents in the area of mobile communications. In 2012, he received the ITU Association of Japan Award for his global contributions to LTE.



### Takahiro Asai

Deputy General Manager, 6G-IOWN Promotion Department, NTT DOCOMO, INC.

He received a B.E. and M.E. in electrical and electronics engineering, and Ph.D in communications and computer engineering from Kyoto University in 1995, 1997, and 2008. In 1997, he joined NTT Mobile Communications Network, Inc. (currently, NTT DOCOMO, INC.). Since then, he has been engaged in the research of signal processing for mobile radio communication.